



# EM Stuffers

Model	Overall Height	Height to Horn	Knee Switch Height	Base Width	Base Depth	Lid Swing Radius	Capacity Litres	Capacity Lbs.
EM-20	43.7"	41.5"	19.7"	16.1"	18.5"	15.6"	20	45
EM-30	47.4"	45.3"	21.7"	18.5"	19.7"	17.3"	30	65



EM-20



EM-30



## FEATURES & BENEFITS

- ALL STAINLESS CONSTRUCTION** For Durable Long Life
- SIDE MOUNTED KNEE SWITCH** For More Comfortable Operation & Less Knee Strain
- POWERFUL MOTOR** For Faster Stuffing with Stiff Products
- VARIABLE SPEED WITH BUILT IN PRESSURE GAUGE** For Precise Product Control & Power (fig 1.)
- ENCLOSED OIL RESERVOIR** Eliminates Spills while Moving
- THREE STUFFING HORNS INCLUDED** For Maximum Flexibility (12, 15, 20, 30 or 40 mm)
- WATER TIGHT CONSTRUCTION** For Carefree Hose-Down Cleaning
- AUTO PISTON DECOMPRESSION WHEN KNEE SWITCH IS RELEASED** For Less Product Overstuffing & Bleedoff
- REMOVABLE PISTON & SWING-OUT LID** For Easy Cleaning (fig 2.)
- SMOOTH PRODUCT DISCHARGE PATH** Eliminates Clogging & Product Discoloration
- KNEE SWITCH "AUTO-ON"** For Noise Free Idle Time (3 phase only)

## OPTIONS:

- MANUAL PORTION CONTROL HEAD** For Precise Filling of Bags & Casings
- ANTI-TILT TROLLEY & CASTORS** For Safe, Stable, Easy, Strain-Free Moving (fig. 3)
- STAINLESS STEEL LID & PISTON** For USDA Approved Operations



Manual Portion Control Head



(fig 1.)



(fig 2.)



(fig 3.)

## Technical Data

Motors:  
 3 Phase, 220-400V, 60Hz  
 1 Phase, 220V, 60Hz  
 1 Phase, 110V, 60Hz  
 Net Weight:

## Model

HP / Amps  
 HP / Amps  
 HP / Amps  
 LBS.

## EM-20

1.25 / 4.5  
 1.50 / 10.5  
 1.50 / 21  
 238

## EM-30

1.75 / 5.8  
 2.50 / 11.5  
 2.0 / 26  
 256



411 Eichelberger Street  
 St. Louis, MO 63111  
 (877) 677-7761  
 Fax (314) 353-6655

Mainca USA Inc. reserves the right to alter any specification without prior notice.



Mainca USA Headquarters  
 St. Louis, MO USA



Mainca World Headquarters  
 Barcelona, SPAIN